

§ 28.250**46 CFR Ch. I (10-1-08 Edition)**

NOTE: Each vessel which uses radio equipment to meet the communication requirements of this section must have a Ship Radio Station License issued by the Federal Communications Commission, as set forth in 47 CFR part 80.

- (i) All communication equipment must be provided with an emergency source of power that complies with § 28.375.

§ 28.250 High water alarms.

On a vessel 36 feet (11.8 meters) or more in length, a visual and audible alarm must be provided at the operating station to indicate high water level in each of the following normally unmanned spaces:

- (a) A space with a through-hull fitting below the deepest load waterline, such as the lazarette;
- (b) A machinery space bilge, bilge well, shaft alley bilge, or other space subject to flooding from sea water piping within the space; and
- (c) A space with a non-watertight closure, such as a space with a non-watertight hatch on the main deck.

§ 28.255 Bilge pumps, bilge piping, and dewatering systems.

(a) Each vessel must be equipped with a bilge pump and bilge piping capable of draining any watertight compartment, other than tanks and small buoyancy compartments, under all service conditions. Large spaces, such as enginerooms must be fitted with more than one suction line.

(b) In addition to the requirements of paragraph (a) of this section, a space used in the sorting or processing of fish in which water is used must be fitted with dewatering system capable of dewatering the space under normal conditions of list and trim at the same rate as water is introduced. Pumps used as part of the processing of fish do not count for meeting this requirement. The dewatering system must be interlocked with the pump(s) supplying water to the space, so that in the event of failure of the dewatering system, the water supply is inactivated.

(c) Except as provided by paragraph (f) of this section, each vessel 79 feet (24 meters) or more in length must be equipped with a fixed, self-priming,

powered, bilge pump connected to a bilge manifold.

(d) If a bilge pump required by paragraph (a) of this section is portable, it must be provided with a suitable suction hose of adequate length to reach the bilges of each watertight compartment it must serve and with a discharge hose of adequate length to ensure overboard discharge. A portable pump must be capable of dewatering each space it serves at a rate of at least 2 inches (51 millimeters) of water depth per minute.

(e) Except for a fire pump required by § 28.315, a bilge pump may be used for other purposes.

(f) Except where an individual pump is provided for a separate space or for a portable pump, each individual bilge suction line must be led to a manifold. Each bilge suction line must be provided with a stop valve at the manifold and a check valve at some accessible point in the bilge line to prevent unintended flooding of a space.

(g) Each bilge suction line and dewatering system suction must be fitted with a suitable strainer to prevent clogging of the suction line. Strainers must have an open area of not less than three times the open area of the suction line.

(h) Each vessel must comply with the oil pollution prevention requirements of 33 CFR parts 151 and 155.

§ 28.260 Electronic position fixing devices.

Each vessel 79 feet (24 meters) or more in length must be equipped with an electronic position fixing device capable of providing accurate fixes for the area in which the vessel operates.

§ 28.265 Emergency instructions.

(a) Except as provided in paragraphs (b) and (c) of this section, each vessel must have emergency instructions posted in conspicuous locations accessible to the crew.

(b) The instructions identified in paragraphs (d)(6), (d)(7), (d)(8), and (d)(9) of this section, may be kept readily available as an alternative to posting.

(c) On a vessel which operates with less than 4 individuals on board, the emergency instructions may be kept

- readily available as an alternative to posting.
- (d) The emergency instructions required by this section must identify at least the following information, as appropriate for the vessel:
- (1) The survival craft embarkation stations aboard the vessel and the survival craft to which each individual is assigned;
 - (2) The fire and emergency signal and the abandon ship signal;
 - (3) If immersion suits are provided, the location of the suits and illustrated instructions on the method for donning the suits;
 - (4) Procedures for making a distress call, such as:
 - (i) Make sure your communication equipment is on.
 - (ii) Select 156.8 MHz (VHF channel 16), 2182 kHz, or other distress frequency used in your area of operation. Note: VHF channel 16 and 2182 kHz on SSB are for emergency and calling purposes only.
 - (iii) Press microphone button and speaking slowly—clearly—calmly say: “Mayday—Mayday—Mayday”
 - (iv) Say: “This is the M/V (Insert name of your vessel), (Insert name of your vessel), (Insert name of your vessel). Over.”
 - (v) Release the microphone button briefly and listen for acknowledgment. If no one answers, repeat steps in paragraphs (d)(4) (iii) and (iv) of this section.
 - (vi) If there is still no answer, or if the Coast Guard or another vessel responds, say: “Mayday—This is the M/V (Insert Name of Your Vessel).”
 - (vii) Describe your position using latitude and longitude coordinates, LORAN coordinate, or range and bearing from a known point.
 - (viii) State the nature of the distress.
 - (ix) Give number of individuals aboard and the nature of any injuries.
 - (x) Estimate the present seaworthiness of your vessel.
 - (xi) Describe your vessel: (Insert length, color, hull type, trim, masts, power, and any additional distinguishing features).
 - (xii) Say: “I will be listening on Channel 16/2182 (or other channel monitored).”
 - (xiii) End message by saying: “This is (insert vessel's name and call sign).”
 - (xiv) If your situation permits, stand by the radio to await further communication with the Coast Guard or another vessel. If no answer, repeat, then try another channel.
- (5) Essential action that must be taken in an emergency by each individual, such as:
- (i) Making a distress call.
 - (ii) Closing of hatches, airports, watertight doors, vents, scuppers, and valves for intake and discharge lines which penetrate the hull, stopping of fans and ventilation systems, and operation of all safety equipment.
 - (iii) Preparing and launching of survival craft and rescue boats.
 - (iv) Fighting a fire.
 - (v) Mustering of personnel including—
 - (A) Seeing that they are properly dressed and have put on their lifejackets or immersion suits; and
 - (B) Assembling personnel and directing them to their appointed stations.
 - (vi) Manning of fire parties assigned to deal with fires.
 - (vii) Special duties required for the operation of fire fighting equipment.
- (6) The procedures for rough weather at sea, crossing hazardous bars, flooding, and anchoring of the vessel, such as:
- (i) Close all watertight and weather-tight doors, hatches and airports to prevent taking water aboard or further flooding in the vessel.
 - (ii) Keep bilges dry to prevent loss of stability due to water in bilges. Use power driven bilge pump, hand pump, and buckets to dewater.
 - (iii) Align fire pumps to use as bilge pumps, if possible.
 - (iv) Check all intake and discharge lines which penetrate the hull for leakage.
 - (v) Personnel should remain stationary and evenly distributed.
 - (vi) Personnel should don lifejackets and immersion suits if the going becomes very rough, the vessel is about to cross a hazardous bar, or when otherwise instructed by the master or individual in charge of the vessel.
- (7) The procedures for anchoring the vessel.

§ 28.270**46 CFR Ch. I (10-1-08 Edition)**

- (8) The procedures to be used in the event an individual falls overboard, such as:
- (i) Throw a ring life buoy as close to the individual as possible;
 - (ii) Post a lookout to keep the individual in the water in sight;
 - (iii) Launch the rescue boat and maneuver it to pick up the individual in the water;
 - (iv) Have a crewmember put on a lifejacket or immersion suit, attach a safety line to the crewmember, and have the crewmember standby to jump into the water to assist in recovering the individual in the water if necessary;
 - (v) If the individual overboard is not immediately located, notify the Coast Guard and other vessels in the vicinity; and
 - (vi) Continue searching until released by the Coast Guard.
- (9) Procedures for fighting a fire, such as:
- (i) Shut off air supply to the fire—close hatches, ports, doors, ventilators, and similar openings;
 - (ii) Deenergize the electrical systems supplying the affected space, if possible;
 - (iii) Immediately use a portable fire extinguisher or use water for fires in ordinary combustible materials. Do not use water on electrical fires.
 - (iv) If the fire is in a machinery space, shut off the fuel supply and ventilation system and activate the fixed extinguishing system, if installed.
 - (v) Maneuver the vessel to minimize the effect of wind on the fire.
 - (vi) If unable to control the fire, immediately notify the Coast Guard and other vessels in the vicinity.
 - (vii) Move personnel away from the fire, have them put on lifejackets, and if necessary, prepare to abandon the vessel.

§ 28.270 Instruction, drills, and safety orientation.

(a) *Drills and instruction.* The master or individual in charge of each vessel must ensure that drills are conducted and instruction is given to each individual on board at least once each month. Instruction may be provided in conjunction with drills or at other times and places provided it ensures

that each individual is familiar with their duties and their responses to at least the following contingencies:

- (1) Abandoning the vessel;
 - (2) Fighting a fire in different locations on board the vessel;
 - (3) Recovering an individual from the water;
 - (4) Minimizing the effects of unintentional flooding;
 - (5) Launching survival craft and recovering lifeboats and rescue boats;
 - (6) Donning immersion suits and other wearable personal flotation devices;
 - (7) Donning a fireman's outfit and a self-contained breathing apparatus, if the vessel is so equipped;
 - (8) Making a voice radio distress call and using visual distress signals;
 - (9) Activating the general alarm; and
 - (10) Reporting inoperative alarm systems and fire detection systems.
- (b) *Participation in drills.* Drills must be conducted on board the vessel as if there were an actual emergency and must include participation by all individuals on board, breaking out and using emergency equipment, testing of all alarm and detection systems, donning protective clothing, and donning immersion suits, if the vessel is so equipped.
- (c) *Training.* No individual may conduct the drills or provide the instructions required by this section unless that individual has been trained in the proper procedures for conducting the activity.
- (d) The viewing of videotapes concerning at least the contingencies listed in paragraph (a) of this section, whether on board the vessel or not, followed by a discussion led by an individual familiar with these contingencies will satisfy the requirement for instruction but not the requirement for drills in paragraph (b) of this section or for the safety orientation in paragraph (e) of this section.
- (e) *Safety orientation.* The master or individual in charge of a vessel must ensure that a safety orientation is given to each individual on board that has not received the instruction and has not participated in the drills required by paragraph (a) of this section before the vessel may be operated.