COMMERCIAL FISHING VESSEL SAFETY EXAMINATION SUPPLEMENTS U. S. COAST GUARD

SUPPLEMENT 6 (Aleutian Trade Act)				
Vessel Name:	I.D. Number:			
ALEUTIAN TRADE ACT FISH TENDERS (NEWLY CONSTRUCTED OR ATA VESSEL'S UNDERGONE A MAJOR				
CONVERSION AFTER 15 SEP 1991 MUST ALSO COMPLY WITH ADDITIONAL REQUIREMENTS OF SUBPART D)				
46 USC 8104(o)	Watches for the licensed individuals and crewmembers: ☐ 3 watches; or Existing vessels that operated in ATA prior to September 9, 1990: ☐ 2 watches	O Yes	O No	O N/A
46 CFR 28.805	Gates for Launching of Survival Craft weighs more than 110 lbs	O Yes	O No	O N/A
46 CFR 28.810	Deck Rails, Lifelines, Storm Rails and Hand Grabs	O Yes	O No	O N/A
46 CFR 28.815	Bilge Pumps, Piping, and Dewatering: Primary: □ ≥ 50 GPM □ Connected to a bilge manifold □ Capable of draining any watertight compartment □ Large spaces (Engine Rm./Cargo Holds) >1 suction. □ Stop valve at manifold □ Check valves on suction lines □ Strainers of appropriate size on each suction line Secondary: □ Independent source of power (fixed system) meeting above, OR □ Portable Bilge Pump: □ ≥ 50 GPM □ Self priming □ Adequate suction hose w/check valve/strainer □ Adequate discharge hose □ Capable of attaching to fixed			O N/A
46 CFR 28.820	Fire Pumps, Mains, Hydrants and Hoses: Primary: ☐ Fixed fire pump with ≥ 50 GPM and 60 psi at pump outlet, ☐ Effective stream from hose connected at highest outlet. ☐ Sufficient number of hydrants Each hydrant: ☐ 1.5" diameter length of hose ☐ Spanner wrench ☐ Hose rack or other stowage device ☐ Nozzle Portable: ☐ ≥ 50 GPM and 60 psi at pump outlet and throw of at least 39.4 ft ☐ Portable dewatering pump may be used to meet this requirement.	O Yes	O No	O N/A
46 CFR 28.825	Excess Fire Detection and Protection Equipment	O Yes	O No	O N/A
46 CFR 28.830	Fire Detection System—Smoke alarms in each accom. space; meets UL-217			O N/A
46 CFR 28.835	Fuel Systems ☐ Portable Fuel Systems Prohibition ☐ Vent pipes for integral tanks ☐ Fuel Restrictions ☐ Fuel Piping			O N/A
46 CFR 28.840	Means for stopping pumps, ventilation, and machinery	1		O N/A
46 CFR 28.845	Electrical Standards—General			O N/A
46 CFR 28.850	Main Source of Electrical Power	O Yes	O No	O N/A
46 CFR 28.855	Electrical Distribution Systems			O N/A
46 CFR 28.860	Overcurrent Protection and Switched Circuits	O Yes	O No	O N/A
46 CFR 28.865	Wiring Methods and Materials	O Yes	O No	O N/A
46 CFR 28.870	Emergency Source of Electrical Power	O Yes	O No	O N/A
46 CFR 28.875	Radar & Depth Sounder: At operating station	ł		O N/A
46 CFR 28.880	Hydraulic Equipment	O Yes	O No	O N/A
46 CFR 28.885	Cargo Gear: ☐ SWL marked on each boom, crane, or derrick. ☐ Gear inspected monthly by captain or delegate ☐ Cargo Safety Insp (2 yr) ☐ Records (monthly and 2 yr inspection)			O N/A
46 CFR 28.905	Repairs and alterations: None made without CG notification	O Yes	O No	O N/A
Exam Notes:				